

PS6Si STEREO INPUT PLANTER SPEAKER



Planter Style Indoor/Outdoor Stereo Loudspeaker

6" Weatherproof Planter Loudspeaker



PS6Si

Stock Number FG01264

FEATURES

- Artistically crafted cabinet with shaped MicroPerfTM aluminum grilles look natural and realistic
- 6.5" dual voice coil injection-molded TCC (talc, carbon, and ceramic) filled polypropylene woofer with butyl rubber surround
- Dual 1" fluid-cooled tri-laminate Teteron tweeters mounted at a custom angle for optimum dispersion
- Separate left and right channel inputs provide stereo sound in a single loudspeaker projecting quality stereo sound over a larger area than conventional loudspeakers
- Weatherproof design ensures performance outdoors
- Designed to accommodate live plants
- Dual 3-foot burial-rated connection cables with waterproof wire-nuts to insure trouble free connection
- Can be wired in one-speaker stereo-input mode or two-speaker stereo mode

SPECIFICATIONS

- Dimensions: 19 1/2" W x 19 1/2" H x 19 1/2" D
- Weight: 35 lbs. (15.9 kgs)

Warranty: Two-year

Product Details

RECOMMENDED AMPLIFIER POWER

10 to 100 Watts

NOMINAL IMPEDANCE

- 8 Ohm, in one-speaker stereo mode
- 4 Ohm, in two-speaker stereo mode

WIRING REQUIREMENTS

2-conductor direct burial cable at the following sizes depending on longest length of cable required (2 per speaker in one-speaker stereo mode):

Wire Gauge Maximum Distance

16 60 ft (18 m) 14 100 ft (30 m) 12 160 ft (50 m)

TEMPERATURE EXTREMES

-50° to 185° Fahrenheit

-45° to 85° Celsius